

Open eClass - Σφαλιματα #290

MySQL 5.7.10 issues

02/02/2016 12:07 - Panayotis Katsaloulis

Status:	Κλειστο	Start date:	02/02/2016
Priority:	Κανονικη	Due date:	
Assignee:		% Done:	50%
Category:		Estimated time:	0.00 hour
Target version:		Spent time:	0.00 hour

Description

Με τη MySQL υπαρχουν ακομα θεματα, τα αναφερω εδω για να τα εχουμε ως αναφορα για να τα επιλυσουμε.

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 36 : Unable to execute statement:"Unknown system variable 'storage_engine'", sqlstate:"1193", errornum:"HY000", statement:"SET storage_engine = InnoDB", elapsed:0.001235
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 731 : Unable to execute statement:"Invalid default value for 'ltime_alive'", sqlstate:"1067", errornum:"42000", statement:"CREATE TABLE IF NOT EXISTS `wiki_locks` ( `ptitle` VARCHAR(255) NOT NULL DEFAULT ' ', `wiki_id` INT(11) UNSIGNED NOT NULL, `uid` MEDIUMINT(8) UNSIGNED NOT NULL DEFAULT 0, `ltime_created` TIMESTAMP NOT NULL, `ltime_alive` TIMESTAMP NOT NULL, PRIMARY KEY (ptitle, wiki_id) ) DEFAULT CHARACTER SET=utf8", elapsed:0.000550000000000005
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1065 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `add_node`", elapsed:0.001768
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1079 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `add_node` (IN name TEXT CHARSET utf8, IN parentlft INT(11), IN p_code VARCHAR(20) CHARSET utf8, IN p_allow_course BOOLEAN, IN p_allow_user BOOLEAN, IN p_order_priority INT(11)) LANGUAGE SQL BEGIN DECLARE lft, rgt INT(11); SET lft = parentlft + 1; SET rgt = parentlft + 2; CALL shift_right(parentlft, 2, 0); INSERT INTO `hierarchy` (name, lft, rgt, code, allow_course, allow_user, order_priority) VALUES (name, lft, rgt, p_code, p_allow_course, p_allow_user, p_order_priority); END", elapsed:0.001726
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1081 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `add_node_ext`", elapsed:0.00056499999999998
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1095 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `add_node_ext` (IN name TEXT CHARSET utf8, IN parentlft INT(11), IN p_code VARCHAR(20) CHARSET utf8, IN p_number INT(11), IN p_generator INT(11), IN p_allow_course BOOLEAN, IN p_allow_user BOOLEAN, IN p_order_priority INT(11)) LANGUAGE SQL BEGIN DECLARE lft, rgt INT(11); SET lft = parentlft + 1; SET rgt = parentlft + 2; CALL shift_right(parentlft, 2, 0); INSERT INTO `hierarchy` (name, lft, rgt, code, number, generator, allow_course, allow_user, order_priority) VALUES (name, lft, rgt, p_code, p_number, p_generator, p_allow_course, p_allow_user, p_order_priority); END", elapsed:0.000600000000000002
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1097 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `update_node`", elapsed:0.000474
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1110 : Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlstate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `update_node` (IN p_id INT(11), IN p_name TEXT CHARSET utf8, IN nodelft INT(11), IN p_lft INT(11), IN p_rgt INT(11), IN parentlft INT(11), IN p_code VARCHAR(20) CHARSET utf8, IN p_allow_course BOOLEAN, IN p_allow_user BOOLEAN, IN p_order_priority INT(11)) LANGUAGE SQL BEGIN UPDATE `hierarchy` SET name = p_name, lft = p_lft, rgt = p_rgt, code = p_code, allow_course = p_allow_course, allow_user = p_allow_user, order_priority = p_o
```

```
rder_priority WHERE id = p_id; IF nodelft <> parentlft THEN CALL move_nodes(nodelft, p_lft, p_rgt)
; END IF; END", elapsed:0.001049
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1112 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `delete_node`", elapsed:0.000427
00000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1122 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `delete_node` (IN p_id INT(11)) LANGUAGE
SQL BEGIN DECLARE p_lft, p_rgt INT(11); SELECT lft, rgt INTO p_lft, p_rgt FROM `hierarchy` WHERE
id = p_id; DELETE FROM `hierarchy` WHERE id = p_id; CALL delete_nodes(p_lft, p_rgt); END", elapsed
:0.00053600000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1124 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `shift_right`", elapsed:0.000366
00000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1139 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `shift_right` (IN node INT(11), IN shift
INT(11), IN maxrgt INT(11)) LANGUAGE SQL BEGIN IF maxrgt > 0 THEN UPDATE `hierarchy` SET rgt = rg
t + shift WHERE rgt > node AND rgt <= maxrgt; ELSE UPDATE `hierarchy` SET rgt = rgt + shift WHERE
rgt > node; END IF; IF maxrgt > 0 THEN UPDATE `hierarchy` SET lft = lft + shift WHERE lft > node A
ND lft <= maxrgt; ELSE UPDATE `hierarchy` SET lft = lft + shift WHERE lft > node; END IF; END", el
apsed:0.00042200000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1141 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `shift_left`", elapsed:0.0002610
0000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1156 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `shift_left` (IN node INT(11), IN shift
INT(11), IN maxrgt INT(11)) LANGUAGE SQL BEGIN IF maxrgt > 0 THEN UPDATE `hierarchy` SET rgt = rgt
- shift WHERE rgt > node AND rgt <= maxrgt; ELSE UPDATE `hierarchy` SET rgt = rgt - shift WHERE r
gt > node; END IF; IF maxrgt > 0 THEN UPDATE `hierarchy` SET lft = lft - shift WHERE lft > node AN
D lft <= maxrgt; ELSE UPDATE `hierarchy` SET lft = lft - shift WHERE lft > node; END IF; END", ela
psed:0.0003429999999999998
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1158 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `shift_end`", elapsed:0.000306
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1165 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `shift_end` (IN p_lft INT(11), IN p_rgt
INT(11), IN maxrgt INT(11)) LANGUAGE SQL BEGIN UPDATE `hierarchy` SET lft = (lft - (p_lft - 1)) +
maxrgt, rgt = (rgt - (p_lft - 1)) + maxrgt WHERE lft BETWEEN p_lft AND p_rgt; END", elapsed:0.0004
16
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1167 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `get_maxrgt`", elapsed:0.000467
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1172 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `get_maxrgt` (OUT maxrgt INT(11)) LANGUA
GE SQL BEGIN SELECT rgt INTO maxrgt FROM `hierarchy` ORDER BY rgt DESC LIMIT 1; END", elapsed:0.00
034600000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1174 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `get_parent`", elapsed:0.000501
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1179 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `get_parent` (IN p_lft INT(11), IN p_rgt
INT(11)) LANGUAGE SQL BEGIN SELECT * FROM `hierarchy` WHERE lft < p_lft AND rgt > p_rgt ORDER BY
lft DESC LIMIT 1; END", elapsed:0.000393
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1181 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `delete_nodes`", elapsed:0.00029
6999999999999
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1191 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `delete_nodes` (IN p_lft INT(11), IN p_r
gt INT(11)) LANGUAGE SQL BEGIN DECLARE node_width INT(11); SET node_width = p_rgt - p_lft + 1; DEL
ETE FROM `hierarchy` WHERE lft BETWEEN p_lft AND p_rgt; UPDATE `hierarchy` SET rgt = rgt - node_wi
dth WHERE rgt > p_rgt; UPDATE `hierarchy` SET lft = lft - node_width WHERE lft > p_lft; END", elap
sed:0.00034700000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1193 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"DROP PROCEDURE IF EXISTS `move_nodes`", elapsed:0.000275
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1218 :
Unable to execute statement:"Cannot load from mysql.proc. The table is probably corrupted", sqlst
ate:"1728", errornum:"HY000", statement:"CREATE PROCEDURE `move_nodes` (INOUT nodelft INT(11), IN
p_lft INT(11), IN p_rgt INT(11)) LANGUAGE SQL BEGIN DECLARE node_width, maxrgt INT(11); SET node_w
idth = p_rgt - p_lft + 1; CALL get_maxrgt(maxrgt); CALL shift_end(p_lft, p_rgt, maxrgt); IF nodelf
t = 0 THEN CALL shift_left(p_rgt, node_width, 0); ELSE CALL shift_left(p_rgt, node_width, maxrgt);
IF p_lft < nodelft THEN SET nodelft = nodelft - node_width; END IF; CALL shift_right(nodelft, nod
e_width, maxrgt); UPDATE `hierarchy` SET rgt = (rgt - maxrgt) + nodelft WHERE rgt > maxrgt; UPDATE
`hierarchy` SET lft = (lft - maxrgt) + nodelft WHERE lft > maxrgt; END IF; END", elapsed:0.000430
00000000001
```

```
In file /Users/teras/Works/Development/WebApps/eClass/server/install/install_db.php on line 1717 :
Unable to execute statement:"Table 'eclass.wiki_locks' doesn't exist", sqlstate:"1146", errornum:
"42S02", statement:"CREATE INDEX `wiki_id` ON wiki_locks(wiki_id)", elapsed:0.00052599999999997
```

History

#1 - 02/02/2016 16:21 - Yannis Exidaridis

- % Done changed from 0 to 50

διορθωθηκαν τα default engine και ο πινακας wiki_locks.

#2 - 26/05/2020 12:14 - Yannis Exidaridis

εχει διορθωθει.

#3 - 26/05/2020 12:14 - Yannis Exidaridis

- Status changed from *Νεα* to *Κλειστο*